

WHAT IS CLAIMED IS:

1. An ink jet recording apparatus comprising:  
a carriage for mounting a recording head for  
effecting recording by discharging recording ink and  
5 for moving said recording head; and  
recovery means for effecting a recovery  
operation with respect to said recording head,  
wherein said recording apparatus is forwarded  
from a manufacturing factory in a condition that said  
10 recording head filled with transporting ink different  
from the recording ink is mounted on said carriage,  
and wherein an on-arrival recovery mode executed by  
said recovery means upon first usage of said  
recording apparatus by the user differs from a normal  
15 recovery mode executed by said recovery means after  
the first usage.
2. An ink jet recording apparatus according to  
claim 1, wherein said apparatus includes suction  
20 means for effecting suction from said recording head  
as recovery means, and suction pressure in ink  
suction from said recording head by means of said  
suction means in said on-arrival recovery mode is set  
to be greater than suction pressure in ink suction in  
25 said normal recovery mode.
3. An ink jet recording apparatus according to

20250930.042202

claim 1, wherein said apparatus includes suction  
means for effecting suction from said recording head  
as recovery means, and a suction amount in ink  
suction from said recording head by means of said  
5 suction means in said on-arrival recovery mode is set  
to be greater than a suction amount in ink suction in  
said normal recovery mode.

4. An ink jet recording apparatus according to  
10 claim 1, wherein said apparatus includes suction  
means for effecting suction from said recording head  
as recovery means, and the number of suction  
operations in ink suction from said recording head by  
means of said suction means in said on-arrival  
15 recovery mode is set to be greater than the number of  
suction operations in ink suction in said normal  
recovery mode.

5. An ink jet recording apparatus according to  
20 claim 1, wherein said on-arrival recovery mode is a  
mode in which one kind of recovery operations in said  
normal recovery mode are executed continuously by  
plural times.

25 6. An ink jet recording apparatus according to  
claim 1, wherein said recovery means includes suction  
means for effecting suction from said recording head,

and the number of idle suction operations for  
discharging the ink from a cap by driving said  
suction means in a communication condition between  
the interior of said cap and the atmosphere upon ink  
5 suction from said recording head by said suction  
means in said on-arrival recovery mode is set to be  
greater than the number of idle suction operations in  
said normal recovery mode.

10 7. An ink jet recording apparatus according to  
claim 1, wherein said recovery means includes suction  
means for effecting suction from said recording head  
and a wiper for wiping said recording head, and the  
number of wiping operations of said wiper after ink  
15 suction from said recording head by said suction  
means in said on-arrival recovery mode is set to be  
greater than the number of wiping operations after  
ink suction in said normal recovery mode.

20 8. An ink jet recording apparatus according to  
claim 1, wherein said recovery means includes a wiper  
for wiping said recording head and a cleaner for  
cleaning said wiper, and the number of cleaning  
operations of said cleaner after the wiping of said  
25 wiper in said on-arrival recovery mode is set to be  
greater than the number of cleaning operations after  
the wiping in said normal recovery mode.

10050930.013002

9. An ink jet recording apparatus according to claim 1, wherein said recovery means includes suction means for effecting suction from said recording head and a wiper for wiping said recording head, and, in  
5 said on-arrival recovery mode, after ink suction from said recording head is firstly effected by said suction means, wiping of said wiper is effected.

10. An ink jet recording apparatus according to  
10 claim 1, wherein viscosity of the transporting ink is greater than that of the recording ink.

11. An ink jet recording apparatus according to  
15 claim 1, wherein the recording ink includes color material and the transporting ink does not include color material or has color component fewer than that of the recording ink.

12. An ink jet recording apparatus comprising:  
20 a carriage for mounting a recording head for effecting recording by discharging recording ink and for moving said recording head; and

recovery means for effecting a recovery operation with respect to said recording head,  
25 wherein said recording apparatus is forwarded from a manufacturing factory in a condition that said recording head filled with transporting ink different

202210-025000T

5

10

15

20

ta

25

14. An ink jet recording apparatus according to  
claim 1, 12 or 13, wherein said recording head  
includes an ink discharging electrothermal converter  
for generating thermal energy utilized for  
5 discharging the ink.

15. An ink jet recording apparatus according to  
claim 14, wherein the ink is discharged by utilizing  
pressure change based on growth of a bubble created  
10 by film boiling caused by the thermal energy  
generated by said electrothermal converter.

16. An ink jet recording apparatus according to  
claim 1, 12 or 13, wherein the transporting ink is  
15 heated by an ink temperature maintaining  
electrothermal converter within said recording head  
before or during the ink suction by said suction  
means in said on-arrival recovery mode.

20 17. An ink jet recording apparatus according to  
claim 1, 12 or 13, wherein the transporting ink is  
heated by an ink discharging electrothermal converter  
within said recording head before or during the ink  
suction by said suction means in said on-arrival  
25 recovery mode.

18. An ink jet recording apparatus according to

20221010 08505007

claim 1, 12 or 13, wherein the transporting ink is  
heated by an ink temperature maintaining  
electrothermal converter and an ink discharging  
electrothermal converter within said recording head  
5 before or during the ink suction by said suction  
means in said on-arrival recovery mode.

19. An ink jet recording apparatus according to  
claim 1, 12 or 13, wherein the transporting ink is  
10 discharged by an ink discharging electrothermal  
converter within said recording head before or during  
the ink suction by said suction means in said on-  
arrival recovery mode.

20. An ink jet recording apparatus according to  
claim 1, 12 or 13, wherein the transporting ink is  
heated by an ink temperature maintaining  
electrothermal converter within said recording head  
and the transporting ink is discharged by an ink  
20 discharging electrothermal converter during the ink  
suction by said suction means in said on-arrival  
recovery mode.

21. An ink jet recording apparatus according to  
25 claim 1, 12 or 13, wherein the transporting ink is  
heated by an ink temperature maintaining  
electrothermal converter within said recording head

20250930-0330T

from before the ink suction to the end of the ink suction by said suction means in said on-arrival recovery mode.

5           22. An ink jet recording apparatus according to claim 1, 12 or 13, wherein the transporting ink is heated by an ink discharging electrothermal converter within said recording head from before the ink suction to the end of the ink suction by said suction  
10 means in said on-arrival recovery mode.

          23. An ink jet recording apparatus according to claim 1, 12 or 13, wherein the transporting ink is heated by an ink temperature maintaining  
15 electrothermal converter and an ink discharging electrothermal converter within said recording head from before the ink suction to the end of the ink suction by said suction means in said on-arrival recovery mode.

20           24. An ink jet recording apparatus according to claim 1, 12 or 13, wherein the transporting ink is discharged by an ink discharging electrothermal converter within said recording head from before the  
25 ink suction to the end of the ink suction by said suction means in said on-arrival recovery mode.

10050930-01220



25. An ink jet recording apparatus according to claim 1, 12 or 13, wherein the transporting ink is heated by an ink temperature maintaining electrothermal converter and the transporting ink is discharged by an ink discharging electrothermal converter within said recording head form before the ink suction to the end of the ink suction by said suction means in said on-arrival recovery mode.

26. An ink jet recording apparatus according to claim 1, 12 or 13, wherein, when the transporting ink is heated and discharged by an ink discharging electrothermal converter within said recording head from before the ink suction to the end of the ink suction by said suction means in said on-arrival recovery mode, an input signal value, frequency, ink color to be inputted and a discharge port can be selected appropriately, and any input signal value, frequency and ink color can be inputted to said ink temperature holding electrothermal converter of said recording head.

27. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising time counting means for counting an elapsed time from the forwarding.

28. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising time reading means for reading the elapsed time from the forwarding.

5

29. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising control means for judging and determining a heating amount of said recording head on the basis of the elapsed time from the forwarding.

10

30. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising temperature history storing means for storing temperature history from the forwarding.

15

31. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising temperature history reading means for reading temperature history from the forwarding.

20

32. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising heating control means for judging and determining a heating amount of said recording head on the basis of temperature history from the forwarding.

25

20250904 09:05:00

33. An ink jet recording apparatus according to claim 32, wherein a heating temperature for each color can be set by said heating control means.

5           34. An ink jet recording apparatus according to claim 1, 12 or 13, further comprising storing means capable of re-writing and calling an elapsed time and temperature history from the forwarding.

10           35. An ink jet recording apparatus according to claim 12 or 13, wherein viscosity of the transporting ink is greater than that of the recording ink.

15           36. A method for handling an ink jet recording apparatus comprising a carriage for mounting a recording head for effecting recording by discharging recording ink and for moving said recording head, and recovery means for effecting a recovery operation with respect to said recording head, the method  
20 comprising the steps of:

          forwarding said ink jet recording apparatus from a manufacturing factory in a condition that said recording head filled with transporting ink different from the recording ink is mounted on said carriage;  
25 and

          executing an on-arrival recovery mode different from a normal recovery mode executed by said recovery

20250930.012200

means after first usage of said recording apparatus by the user by means of said recovery means upon the first usage, with respect to said recording head.

5           37. A method for handling an ink jet recording apparatus comprising a carriage for mounting a recording head for effecting recording by discharging recording ink and for moving said recording head, and recovery means for effecting a recovery operation  
10 with respect to said recording head, the method comprising the steps of:

            forwarding said ink jet recording apparatus from a manufacturing factory in a condition that said recording head filled with transporting ink different  
15 from the recording ink is mounted on said carriage; and

            executing an on-arrival recovery mode same as a recovery mode executed upon exchange of said recording head among a plurality of recovery modes  
20 executed by said recovery means after first usage of said recording apparatus by the user by means of said recovery means upon the first usage, with respect to said recording head.

25           38. A method for handling an ink jet recording apparatus comprising a carriage for mounting a recording head for effecting recording by discharging

20250930 012200

recording ink and for moving said recording head, and  
a mounting section for mounting an ink tank for  
storing the recording ink to be supplied to said  
recording head, the method comprising the steps of:

5           forwarding said ink jet recording apparatus from  
a manufacturing factory in a condition that said  
recording head filled with transporting ink different  
from the recording ink is mounted on said carriage;  
and

10           emitting alarm to the user of said recording  
apparatus if the fact that the said tank is not  
mounted on said mounting section upon first usage of  
said recording apparatus by the user is detected.

202210 06505001